

Material : UL Approved Nylon6/6, 94V-2


All nylon, one-piece construction-up to 250 lbs (114kgs) min. loop tensile strength

Operating temperature : -40°C to 85°C (-40°F to 185°F)

Heat stabilized from -40°C to 105°C (-40°F to 221°F)

Specification : UL approved, UV, Heat Resistant, Non-corrosive, Self-extinguishing

Color are available



Part Number		Length	Width	Max. Bundle Diameter	Min. Loop Tensile Strength
1000 pcs / bag	100 pcs / bag	mm (inch)	mm (inch)	mm (inch)	kg (lbs)
P1000-0001	P1000-0027	80 (3.15)	2.4 (.09)	15 (.59)	8.0 (17-5/8)
P1000-0002	P1000-0028	90 (3.54)		16 (.63)	
P1000-0003	P1000-0029	100 (4.0)	2.5 (.10)	22 (.87)	8.1(18)
P1000-0004	P1000-0030	120 (4.72)		30 (1.18)	
P1000-0005	P1000-0031	140 (5.51)		33 (1.30)	
P1000-0006	P1000-0032	160 (6.3)		40 (1.57)	
P1000-0007	P1000-0033	205 (8.00)		55 (2.17)	
P1000-0008	P1000-0034	250 (9.84)	2.8 (.11)	65 (2.56)	14 (31)
P1000-0009	P1000-0035	300 (11.81)		76 (2.99)	
P1000-0010	P1000-0036	121 (4.76)	3.5 (.14)	30 (1.18)	18.2 (40)
P1000-0011	P1000-0037	140 (5.51)		33 (1.30)	
P1000-0012	P1000-0038	150 (5.91)		35 (1.38)	
P1000-0013	P1000-0039	180 (7.09)		44 (1.73)	
P1000-0014	P1000-0040	203 (8.00)		53 (2.09)	
P1000-0015	P1000-0041	250 (9.84)		65 (2.56)	
P1000-0016	P1000-0042	300 (11.81)		76 (2.99)	
P1000-0017	P1000-0043	370 (14.57)		102 (4.02)	
P1000-0018	P1000-0044	120 (4.72)	4.8 (.19)	24 (.94)	22.2 (50)
P1000-0019	P1000-0045	160 (6.30)		38 (1.50)	
P1000-0020	P1000-0046	188 (7.40)		46 (1.81)	
P1000-0021	P1000-0047	200 (7.87)		50 (1.97)	
P1000-0022	P1000-0048	215 (8.46)		53 (2.09)	
P1000-0023	P1000-0049	250 (9.84)		60 (2.36)	
P1000-0024	P1000-0050	265 (10.43)		65 (2.56)	
P1000-0025	P1000-0051	280 (11.02)		70 (2.76)	
P1000-0026	P1000-0052	300 (11.81)		76 (2.99)	
-	P1000-0053	370 (14.57)		102 (4.02)	
-	P1000-0054	390 (15.35)	105 (4.13)		
-	P1000-0055	430 (16.93)	110 (4.33)		
-	P1000-0056	450 (17.72)	116 (4.57)		
-	P1000-0057	530 (20.87)	140 (5.51)		

Part Number		Length	Width	Max. Bundle Diameter	Min. Loop Tensile Strength
1000 pcs / bag	100 pcs / bag	mm (inch)	mm (inch)	mm (inch)	kg (lbs)
-	P1000-0058	150 (5.91)	7.6 (.30)	33 (1.30)	54.4 (120)
-	P1000-0059	200 (7.87)		50 (1.97)	
-	P1000-0060	250 (9.84)		65 (2.56)	
-	P1000-0061	292 (11.50)		76 (2.99)	
-	P1000-0062	368 (14.49)		102 (4.02)	
-	P1000-0063	760 (30.00)		225 (8.90)	
-	P1000-0064	430 (16.93)	9.0 (.35)	125 (4.92)	79.4 (175)
-	P1000-0065	528 (20.78)		140 (5.51)	
-	P1000-0066	609 (23.97)		178 (7.00)	
-	P1000-0067	710 (27.95)		190 (7.48)	
-	P1000-0068	775 (30.51)		228 (8.98)	
-	P1000-0069	812 (31.97)		239 (9.41)	
-	P1000-0070	912 (35.91)		263 (10.35)	
-	P1000-0071	1020 (40.16)		295 (11.61)	
-	P1000-0072	1220 (48.00)		365(14.37)	