Pro Components

P1500 Series

Pb Lead Free — RoHS Compliant

Specifications

Material: Polyamide 6.6 (PA66)
Color: White or Black
Operating Temperature: -40°C to +85°C
Adhesive: Synthetic rubber with base of polyethylene
Adhesive Operating Temperature: -20°C to +50°C
Flammability: UL 94 V2 (excluding adhesive)
UL Recognized: US and Canada
Fixation Method: Screw Mounting and Adhesive

Features:

For use with 18 and 30 pound cable ties to provide stability when securing bundles.
Secures with rubber based adhesive backing and/or two or four screws.
4 way opening allows cable ties to be installed parallel or perpendicular to wire bundles.

Description:

Pro Components adhesive fastened mounting bases are used with 18 through 150 pound cable ties to provide stability when securing bundles. The mounts are installed using the adhesive backing and/or by securing two or four screws. The 4 way opening allows the cable ties to be inserted parallel or perpendicular to the wire bundles.

Dimensions (Units: MM):

Fig. A

Fig. B

Part Number	L	W	H	Color	Packaging	Fig.
P1500-0002				White	100	
P1500-1002					1000	
P1500-0002 BLACK	19.0	19.0	4.6	Black	100	A
P1500-1002 BLACK					1000	
P1500-0003				White	100	
P1500-0503					500	
P1500-0003 BLACK	28.0	28.0	5.6	Black	100	A
P1500-0503 BLACK					500	
P1500-0004				White	100	
P1500-0254					250	
P1500-0004 BLACK	37.7	37.7	6.9	Black	100	A
P1500-0254 BLACK					250	
P1500-0006				White	100	
P1500-1006					1000	
P1500-0006 BLACK	15.9	15.9	4.1	Black	100	B
P1500-1006 BLACK					1000	

Rev. No. : TV05