



Specifications

- Current Rating: 3 Amps
- Insulator Resistance: 1000 Megohms min.
- Contact Resistance: 20 m ohms max.
- Dielectric Withstanding: AC 600V
- Operating Temperature : -40°C ~ +125°C
- Contact Material: Brass
- Insulator Material: Polyester, UL 94V-0, Nylon-6T
- Contact Plated: See Option, Standard: Full Gold Flash
- *Standard Terminal Dimension: A= 3.00, C= 6.00**

Part Numbering System

SS-H1.5 - XX - A-C - X N

Series

No. of Pins

Terminal Dimensions (mm)

Nil = Standard Dimensions (A= 3.00, C= 6.00)

A = ... , C = ... for Custom Dimensions

Insulator Material:

N = High Temperature Nylon-6T

Contact Plating

Standard Example: SS-H1.5-10-G

(with Standard Terminal Dimension)

A= 3.00, C= 6.00

Custom Example: SS-H1.5-10-2.54-8.13-G

A= 2.54, C= 8.13

* Contact Plating Option	Full Gold Plating	Gold Plated On Contact Area Tin Plated on Solder Area	Full Tin Plating
	G : Gold Flash G10: Gold 10u" G15: Gold 15u" G30: Gold 30u"	S: Gold Flash S10: Gold 10u" S15: Gold 15u" S30: Gold 30u"	T: Tin 100u"

General Tolerance	
X. ± 0.50	X.° ± 5°
.X ± 0.20	.X° ± 2°
.XX ± 0.10	.XX° ± 1°
Units : mm	