

111-04604



Article Number: 111-04604

Description: Standard Cable Tie, 11.6" Long, UL Rated, 40lb Tensile Strength, PA66, Black, 1000/pkg

Base Data	
Local Order Number	T40I0M4
Type	T40I
Color	Black (BK)
Features and benefits	<ul style="list-style-type: none"> <li>• Inside serrations allow for strong hold on cables and wire bundles.</li> <li>• Head design provides high tensile strength with very low insertion force.</li> <li>• Bent tail ensures a quick and simple installation.</li> </ul>
Quantity Per	bag
Brand Family	T-Series
Product Description	HellermannTyton standard cable ties feature inside serrations providing a positive hold onto wire and cable bundles. The head design guarantees high tensile strength, as well as a low insertion force. The bent tail design allows quick and simple installations by hand. For high volume applications, tensioning tools are available to ensure consistent and safe installation.
GLOBAL PART NAME	T40I-PA66-BK
Short Description	Standard Cable Tie, 11.6" Long, UL Rated, 40lb Tensile Strength, PA66, Black, 1000/pkg
Product Dimensions	
Minimum Tensile Strength (Imperial)	40.0lbs
Minimum Tensile Strength (Metric)	180.0N
Length L (Imperial)	11.6"
Length L (Metric)	295.0mm
Fixation Method	None
Identification Plate Position	none
Releasable Closure	No
Variant	Inside Serrated
Width W (Imperial)	0.16"
Width W (Metric)	4.0mm
Bundle Diameter Min. (Imperial)	0.06"
Bundle Diameter Min. (Metric)	1.5mm

111-04604



Product Dimensions	Bundle Diameter Max. (Imperial)	3.15"
	Bundle Diameter Max. (Metric)	80.0mm
Material and Specifications	Material	Polyamide 6.6 (PA66)
	Material Shortcut	PA66
	Flammability	UL 94 V2
	Halogen Free	Yes
	Operating Temperature	-40°F to +185°F (-40°C to +85°C)
	ROHS Compliant	Yes
	UL Listed (US)	Yes
	UL Listed (US and Canada)	Yes
	UL Recognized (US and Canada)	Yes
	UL Recognized (US)	Yes
	Logistic and Packaging	Package Quantity (Imperial)
Package Quantity (Metric)		1000
Customs Number(Schedule B)		3926909987