

111-04311



Article Number: 111-04311

Description: Standard Cable Tie, 14.6" Long, UL Rated, 40lb Tensile Strength, PA66, Natural, 1000/pkg

| Base Data                           |  |
|-------------------------------------|--|
| Local Order Number                  | T40L9M4  |
| Type                                | T40L   |
| Color                               | Natural (NA)   |
| Features and benefits               | <ul style="list-style-type: none"> <li>• Inside serrations allow for strong hold on cables and wire bundles.</li> <li>• Head design provides high tensile strength with very low insertion force.</li> <li>• Bent tail ensures a quick and simple installation.</li> </ul>   |
| Quantity Per                        | bag  |
| Brand Family                        | T-Series   |
| Product Description                 | T-Series Cable Ties feature inside serrations to provide a positive hold on wire and cable bundles. The head design guarantees high tensile strength and a low insertion force. The bent tail design allows quick and simple installations by hand. For high-volume applications, tensioning tools are available to ensure consistent and safe installation. |
| GLOBAL PART NAME                    | T40L-PA66-NA   |
| Short Description                   | Standard Cable Tie, 14.6" Long, UL Rated, 40lb Tensile Strength, PA66, Natural, 1000/pkg   |
| Product Dimensions                  |  |
| Minimum Tensile Strength (Imperial) | 40.0lbs  |
| Minimum Tensile Strength (Metric)   | 180.0N   |
| Length L (Imperial)                 | 14.6"  |
| Length L (Metric)                   | 370.0mm  |
| Fixation Method                     | None   |
| Identification Plate Position       | none   |
| Releasable Closure                  | No   |
| Variant                             | Inside Serrated  |
| Width W (Imperial)                  | 0.16"  |
| Width W (Metric)                    | 4.0mm  |
| Bundle Diameter Min. (Imperial)     | 0.06"  |
| Bundle Diameter Min. (Metric)       | 1.5mm  |

111-04311



|                             |                                 |                                  |
|-----------------------------|---------------------------------|----------------------------------|
| Product Dimensions          | Bundle Diameter Max. (Imperial) | 4.13"                            |
|                             | Bundle Diameter Max. (Metric)   | 104.9mm                          |
| Material and Specifications | Material                        | Polyamide 6.6 (PA66)             |
|                             | Material Shortcut               | PA66                             |
|                             | Flammability                    | UL 94 V2                         |
|                             | Halogen Free                    | Yes                              |
|                             | Operating Temperature           | -40°F to +185°F (-40°C to +85°C) |
|                             | ROHS Compliant                  | Yes                              |
|                             | UL Listed (US)                  | Yes                              |
|                             | UL Listed (US and Canada)       | Yes                              |
|                             | UL Recognized (US and Canada)   | Yes                              |
|                             | UL Recognized (US)              | Yes                              |
|                             | Logistic and Packaging          | Package Quantity (Imperial)      |
| Package Quantity (Metric)   |                                 | 1000                             |
| Customs Number(Schedule B)  |                                 | 3926909987                       |
|                             |                                 |                                  |